

# A six-flux transfer approach for efficient layered materials rendering

JOËL RANDRIANANDRASANA, University of Reims Champagne-Ardenne and United Visual Researchers

PATRICK CALLET, MINES ParisTech

LAURENT LUCAS, University of Reims Champagne-Ardenne



Fig. 1. The model of Belcour [1] suffers from severe energy losses with scattering volumes due to its single-scattering approximation and its lack of support for back-scattering. Our transfer matrix approach overcomes these issues and provides results close to the ground-truth computed with Guo’s stochastic approach [2]. In these examples, a unit depth non-absorbing medium with scattering coefficient  $\sigma_s = 0.755$  and varying Henyey-Greenstein (HG)  $g$  parameters lies on top of a smooth gold substrate. HG  $g$  asymmetry parameter is respectively set to 0.9 and to 0 in the left and right inset.

CCS Concepts: • **Computing methodologies** → **Reflectance modeling**.

Additional Key Words and Phrases: BRDF, Layered materials, Transfer matrix

## ACM Reference Format:

Joël Randrianandrasana, Patrick Callet, and Laurent Lucas. 2020. A six-flux transfer approach for efficient layered materials rendering. In *Proceedings of Siggraph’20 Posters program*. ACM, New York, NY, USA, 1 page. <https://doi.org/10.1145/nnnnnnnn.nnnnnnnn>

## 1 INTRODUCTION

A multi-lobe approach was recently proposed to efficiently handle layered materials rendering [1]. To this end, the author introduces a low-order statistical representation for light-matter interactions and derives new *adding equations* for the framework. However, scattering volumes are poorly supported as the method does not account for back-scattering and resorts to single scattering approximations to avoid expensive *doubling* operations. In practice, this incurs severe energy losses yielding inconsistent dark appearances with increasing volume scattering (Fig. 1). Unfortunately, the adding equations introduced by the author can not be easily extended to handle both forward and backward propagating flux.

We overcome these limitations with an efficient solution based on the *transfer matrix*. Under this formalism, each scattering component of the stack (scattering volume and interface) is described through a lightweight matrix, layering operations reduce to simple matrix products, and total flux accounting for multiple scattering are obtained thanks to matrix operators.

## 2 OUR APPROACH

To achieve high fidelity appearances, we propose to isolate light having undergone one or more scattering events in a medium (secondary flux) from light not scattered by any medium of the structure (primary flux). Moreover, a significant amount of light might be scattered back with highly scattering media. Thus, we propose to split the secondary flux into forward and backward contributions.

Accounting for the vertical directions of propagations in the structure, we thus describe the light distribution at any depth of the structure as a six-flux vector.

The net balance relating the total flux sitting on each side of any component of the structure (or any combination of them) takes a general order-six matrix form for which generic multiple scattering operators are easily derived. We obtain the closed-form transfer matrix of a homogeneous participating medium by approximating the transport occurring in an infinitesimally thin slab and derive the matrix for any arbitrary depth with the exponential matrix method. In the case of an interface, the general transfer matrix further simplifies as no interaction happens between primary and secondary flux.

To compute the shapes of the outgoing lobes with the transfer matrix formalism, we further approximate each light-matter interaction in the structure as Henyey-Greenstein (HG) phase functions convolution as it reduces to simple asymmetry parameters product. In practice, this translates the (energy, mean, variance) statistical representation of the previous work [1] to a (energy, mean, asymmetry) representation. Participating media are easily handled as they are usually described with this function. In the case of interface components, we provide a simple analytical fit for GGX-based rough interfaces and use the inverse fit to convert the extracted HG lobes to microfacet-based lobes. Based on this representation, we compute the shapes of the outgoing primary and secondary flux due to a layer of the stack as weighted sums of HG lobes. Thanks to HG convolution properties, the asymmetry of the resulting lobes can be computed with the same transfer matrix formalism and multiple scattering matrix operators. Starting from the incident medium, we approximate the BRDF of the stack as a mixture of forward and backward GGX lobes sharing the same mean directions following the same iterative approach than previous work [3].

## REFERENCES

- [1] Laurent Belcour. 2018. Efficient rendering of layered materials using an atomic decomposition with statistical operators. *ACM Transactions on Graphics (TOG)* 37, 4 (2018), 73.
- [2] Yu Guo, Miloš Hašan, and Shuang Zhao. 2018. Position-free monte carlo simulation for arbitrary layered BSDFs. In *SIGGRAPH Asia 2018 Technical Papers*. ACM, 279.